

BATTERY SPECIFICATIONS

Premium AGM Factory Activated

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)	CCA @0°F (-18°C)
GT7-B4	6.5	5 ^{7/8} /2 ^{9/16} /3 ^{5/8}	151/66/94		6.0	2.7	4	N/A	N/A	0.6	110
GT9-B4	8	6 ² / ₃ ^{3/4} /4 ^{1/8}	150/70/105		7.5	3.4	4	N/A	N/A	0.8	115
GT12-B4	10	5 ^{7/8} /2 ^{11/16} /5 ^{1/16}	151/70/131		10	4.5	4	N/A	N/A	1.0	180
GT14-B4	12	5 ^{7/8} /2 ^{3/4} /5 ^{11/16}	150/69/145		11	4.9	4	N/A	N/A	1.2	210
GTZ7S	6	4 ^{7/16} /2 ^{3/4} /4 ^{1/8}	113/70/105		4.6	2.1	10	N/A	N/A	0.6	130
GTZ10S	8.6	6 ³ / ₁₆ ^{7/16} /3 ^{11/16}	150/87/93		7.0	3.2	4	N/A	N/A	0.9	190
GTZ12S	11	6 ³ / ₁₆ ^{7/16} /4 ^{3/8}	150/87/110		8.1	3.7	4	N/A	N/A	1.1	210
GTZ14S	11.2	6 ³ / ₁₆ ^{7/16} /4 ^{3/8}	150/87/110		8.6	3.9	4	N/A	N/A	1.1	230
YGIX30	30	6 ⁹ / ₁₆ ⁵ /6 ⁷ / ₈	166/126/175		22	9.9	5	N/A	N/A	3.0	385

Premium AGM

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)	CCA @0°F (-18°C)
GTX4L-BS	3	4 ¹ / ₂ ² / ₁₃ ¹⁶ /3 ³ / ₈	114/71/86		2.9	1.3	5	6.1	0.18	0.4	50
GTX5L-BS	4	4 ¹ / ₂ ² / ₁₃ ¹⁶ /4 ³ / ₁₆	114/71/106		3.5	1.6	5	8.1	0.24	0.5	70
GTX7A-BS	6	6 ³ / ₁₆ ^{7/16} /3 ³ / ₄	150/87/94		5.3	2.4	5	11.1	0.33	0.7	85
GTX7L-BS	6	4 ¹ / ₂ ² / ₁₃ ¹⁶ /5 ³ / ₁₆	114/71/131		5.1	2.3	5	11.1	0.33	0.6	85
GTX9-BS	8	6 ³ / ₁₆ ^{7/16} /4 ³ / ₁₆	150/87/105		5.4	2.4	5	13.5	0.40	0.9	120
GTX12-BS	10	6 ³ / ₁₆ ^{7/16} /5 ¹ / ₈	150/87/130		7.5	3.4	5	20.2	0.60	1.2	180
GTX14-BS	12	6 ³ / ₁₆ ^{7/16} /5 ³ / ₄	150/87/145		8.1	3.7	5	23.6	0.70	1.4	200
GTX14AH-BS	12	5 ⁵ / ₁₆ ³ / ₁₂ ⁶ / ₁₆	134/89/166		8.2	3.7	8	23.6	0.70	1.4	190
GTX14AHL-BS	12	5 ⁵ / ₁₆ ³ / ₁₂ ⁶ / ₁₆	134/89/166		8.2	3.7	8	23.6	0.70	1.4	190
GT16-BS	19	6 ¹⁵ / ₁₆ ⁴ / ₆ ¹ / ₈	176/101/156		10.3	4.7	4	26.3	0.78	4.7	240
GT16L-BS	19	6 ¹⁵ / ₁₆ ⁴ / ₆ ¹ / ₈	176/101/156		10.3	5.1	4	26.3	0.78	4.7	240
GTX18L-BS	20	8 ¹ / ₈ ³ / ₁₆ ⁶ / ₇ ¹⁶	206/91/164		11.2	5.1	4	31.4	0.93	5.1	250
GTX20-BS ¹	18	6 ⁷ / ₈ ³ / ₁₆ ⁶ / ₁ ⁸	175/87/155		11.2	5.1	4	31.4	0.93	1.8	275
GTX20L-BS ¹	18	6 ⁷ / ₈ ³ / ₁₆ ⁶ / ₁ ⁸	175/87/155		11.2	5.1	4	31.4	0.93	1.8	275

¹ The GTX20 series batteries may be used as an optional upgrade, but some modification to the hold down may be necessary. See battery label for retrofit cautions.

CB Series

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)
CB2.5L-C	2.5	3 ³ / ₁₆ ² / ₃ ⁴ / ₁ ⁸	80/70/105		1.7	0.8	-	8.1	.23	0.3
CB2.5L-C-1	2.5	3 ³ / ₁₆ ² / ₃ ⁴ / ₁ ⁸	80/70/105		1.7	0.8	-	8.1	.23	0.3
CB3L-A	3	3 ⁷ / ₈ ² / ₁ ⁴ / ₄ ³ / ₈	98/56/110		2.5	1.1	6	8.1	.23	0.3
CB3L-B	3	3 ⁷ / ₈ ² / ₁ ⁴ / ₄ ³ / ₈	98/56/110		2.5	1.1	6	8.1	.23	0.3
CB4L-A	4	4 ³ / ₄ ² / ₃ ⁴ / ₃ ⁵ / ₈	120/70/92		2.8	1.3	5	10.1	.30	0.4
CB4L-B	4	4 ³ / ₄ ² / ₃ ⁴ / ₃ ⁵ / ₈	120/70/92		2.8	1.3	5	10.1	.30	0.4
CB5L-B	5	4 ³ / ₄ ² / ₃ ⁸ / ₅ ¹ / ₈	120/60/130		3.5	1.6	6	12.2	.36	0.5

BATTERY SPECIFICATIONS

CB Series (continued)

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)
CB7-A	8	5 ^{5/16} /3/5 ^{1/4}	135/75/133		5.1	2.3	6	20.3	0.6	0.8
YB7C-A	8	5 ^{1/8} /3 ^{9/16} /4 ^{1/2}	130/90/114		5.1	2.3	3	20.3	0.6	0.8
CB7L-B	8	5 ^{5/16} /3/5 ^{1/4}	135/75/133		5.1	2.3	11	20.3	0.6	0.8
CB9A-A	9	5 ^{5/16} /3/6 ^{1/8}	135/75/155		5.3	2.4	6	20.3	0.6	0.9
CB9L-A2	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	2.4	4	20.3	0.6	0.9
CB9-B	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	2.4	6	20.3	0.6	0.9
CB9L-B	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	2.4	6	20.3	0.6	0.9
CB10A-A2	11	5 ^{5/16} /3 ^{9/16} /6 ^{1/8}	135/90/155		7.0	3.2	8	27.0	0.8	1.1
CB10L-A2	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	3.2	8	27.0	0.8	1.1
CB10L-B	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	3.2	6	27.0	0.8	1.1
CB10L-B2	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	3.2	8	27.0	0.8	1.1
CB12A-A ¹	12	5 ^{5/16} /3 ^{3/16} /6 ^{5/16}	134/80/160		6.8	3.1	6	27.0	0.8	1.2
CB12AL-A	12	5 ^{5/16} /3 ^{3/16} /6 ^{5/16}	134/80/160		6.8	3.1	6	25.4	0.8	1.2
CB12B-B2	12	6 ^{5/16} /3 ^{9/16} /5 ^{1/8}	160/90/130		7.1	3.2	8	27.0	0.8	1.2
CB12C-A	12	5 ^{5/16} /3 ^{3/16} /6 ^{7/8}	134/80/175		7.1	3.2	4	27.0	0.8	1.2
CB14-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
CB14A-A	14	5 ^{5/16} /3 ^{1/2} /6 ^{15/16}	134/89/176		7.9	3.6	6	30.4	0.9	1.4
CB14A-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{15/16}	134/89/176		7.9	3.6	8	30.4	0.9	1.4
CB14L-A1	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	1	30.4	0.9	1.4
CB14L-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
CB14L-B2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
CB14-B2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
SCB14L-A2 ²	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
SCB14L-B2 ²	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	3.4	8	30.4	0.9	1.4
CB16AL-A2	16	8 ^{1/8} /2 ^{13/16} /6 ^{7/16}	207/71.5/164		8.6	3.9	2	37.2	1.1	1.6
HCB16A-A	16	6 ^{3/8} /7 ^{1/16}	151/91/180		8.5	3.9	7	30.4	0.9	1.6
CB16-B	19	6 ^{7/8} /4/6 ^{1/8}	175/100/155		10.5	4.8	6	40.6	1.2	1.9
CB16L-B ¹	19	6 ^{7/8} /4/6 ^{1/8}	175/100/155		10.5	4.8	6	40.6	1.2	1.9
CB16CL-B	19	6 ^{7/8} /4/6 ^{7/8}	175/100/175		10.1	4.6	4	40.6	1.2	1.9
SCB16L-B ²	19	6 ^{15/16} /4/6 ^{1/8}	175/100/155		9.3	4.2	6	43.9	1.3	1.9
CB18-A	18	7 ^{1/8} /3 ^{9/16} /6 ^{3/8}	180/90/162		9.4	4.3	7	40.6	1.2	1.8
CB18L-A	18	7 ^{1/8} /3 ^{9/16} /6 ^{3/8}	180/90/162		9.4	4.3	7	40.6	1.2	1.8
C50-N18L-A3	20	8 ^{1/8} /2 ^{9/16} /6 ^{3/8}	205/90/162		11.2	5.1	4	47.3	1.4	2.0
C60-N24L-A	28	7 ^{1/4} /4 ^{7/8} /6 ^{7/8}	184/124/175		14.4	6.5	3	57.5	1.7	1.7
CB30L-B	30	6 ^{5/8} /5 ^{3/16} /6 ^{15/16}	168/132/176		14.1	6.4	4	57.5	1.7	3.0

¹ Sensor available for this battery.

² This battery includes a sensor.