

# BATTERY SPECIFICATIONS

## Premium AGM Factory Activated

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)	CCA @0°F (-18°C)
GT7-B4	6.5	5 <sup>7/8</sup> /2 <sup>9/16</sup> /3 <sup>5/8</sup>	151/66/94		6.0	2.7	4	N/A	N/A	0.6	110
GT9-B4	8	6 <sup>2</sup> / <sub>3</sub> <sup>3/4</sup> /4 <sup>1/8</sup>	150/70/105		7.5	3.4	4	N/A	N/A	0.8	115
GT12-B4	10	5 <sup>7/8</sup> /2 <sup>11/16</sup> /5 <sup>1/16</sup>	151/70/131		10	4.5	4	N/A	N/A	1.0	180
GT14-B4	12	5 <sup>7/8</sup> /2 <sup>3/4</sup> /5 <sup>11/16</sup>	150/69/145		11	4.9	4	N/A	N/A	1.2	210
GTZ7S	6	4 <sup>7/16</sup> /2 <sup>3/4</sup> /4 <sup>1/8</sup>	113/70/105		4.6	2.1	10	N/A	N/A	0.6	130
GTZ10S	8.6	6 <sup>3</sup> / <sub>16</sub> <sup>7/16</sup> /3 <sup>11/16</sup>	150/87/93		7.0	3.2	4	N/A	N/A	0.9	190
GTZ12S	11	6 <sup>3</sup> / <sub>16</sub> <sup>7/16</sup> /4 <sup>3/8</sup>	150/87/110		8.1	3.7	4	N/A	N/A	1.1	210
GTZ14S	11.2	6 <sup>3</sup> / <sub>16</sub> <sup>7/16</sup> /4 <sup>3/8</sup>	150/87/110		8.6	3.9	4	N/A	N/A	1.1	230
YGIX30	30	6 <sup>9</sup> / <sub>16</sub> <sup>5</sup> /6 <sup>7</sup> / <sub>8</sub>	166/126/175		22	9.9	5	N/A	N/A	3.0	385

## Premium AGM

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)	CCA @0°F (-18°C)
GTX4L-BS	3	4 <sup>1</sup> / <sub>2</sub> <sup>2</sup> / <sub>13</sub> <sup>16</sup> /3 <sup>3</sup> / <sub>8</sub>	114/71/86		2.9	1.3	5	6.1	0.18	0.4	50
GTX5L-BS	4	4 <sup>1</sup> / <sub>2</sub> <sup>2</sup> / <sub>13</sub> <sup>16</sup> /4 <sup>3</sup> / <sub>16</sub>	114/71/106		3.5	1.6	5	8.1	0.24	0.5	70
GTX7A-BS	6	6 <sup>3</sup> / <sub>16</sub> <sup>1</sup> / <sub>3</sub> <sup>3</sup> / <sub>4</sub>	150/87/94		5.3	2.4	5	11.1	0.33	0.7	85
GTX7L-BS	6	4 <sup>1</sup> / <sub>2</sub> <sup>2</sup> / <sub>13</sub> <sup>16</sup> /5 <sup>3</sup> / <sub>16</sub>	114/71/131		5.1	2.3	5	11.1	0.33	0.6	85
GTX9-BS	8	6 <sup>3</sup> / <sub>16</sub> <sup>7</sup> / <sub>4</sub> <sup>3</sup> / <sub>16</sub>	150/87/105		5.4	2.4	5	13.5	0.40	0.9	120
GTX12-BS	10	6 <sup>3</sup> / <sub>16</sub> <sup>1</sup> / <sub>5</sub> <sup>1</sup> / <sub>8</sub>	150/87/130		7.5	3.4	5	20.2	0.60	1.2	180
GTX14-BS	12	6 <sup>3</sup> / <sub>16</sub> <sup>1</sup> / <sub>5</sub> <sup>3</sup> / <sub>4</sub>	150/87/145		8.1	3.7	5	23.6	0.70	1.4	200
GTX14AH-BS	12	5 <sup>5</sup> / <sub>16</sub> <sup>3</sup> / <sub>12</sub> <sup>6</sup> / <sub>9</sub> <sup>16</sup>	134/89/166		8.2	3.7	8	23.6	0.70	1.4	190
GTX14AHL-BS	12	5 <sup>5</sup> / <sub>16</sub> <sup>3</sup> / <sub>12</sub> <sup>6</sup> / <sub>9</sub> <sup>16</sup>	134/89/166		8.2	3.7	8	23.6	0.70	1.4	190
GT16-BS	19	6 <sup>15</sup> / <sub>16</sub> <sup>4</sup> / <sub>6</sub> <sup>1</sup> / <sub>8</sub>	176/101/156		10.3	4.7	4	26.3	0.78	4.7	240
GT16L-BS	19	6 <sup>15</sup> / <sub>16</sub> <sup>4</sup> / <sub>6</sub> <sup>1</sup> / <sub>8</sub>	176/101/156		10.3	5.1	4	26.3	0.78	4.7	240
GTX18L-BS	20	8 <sup>1</sup> / <sub>8</sub> <sup>3</sup> / <sub>9</sub> <sup>16</sup> /6 <sup>7</sup> / <sub>16</sub>	206/91/164		11.2	5.1	4	31.4	0.93	5.1	250
GTX20-BS <sup>1</sup>	18	6 <sup>7</sup> / <sub>8</sub> <sup>3</sup> / <sub>16</sub> <sup>1</sup> / <sub>6</sub> <sup>1</sup> / <sub>8</sub>	175/87/155		11.2	5.1	4	31.4	0.93	1.8	275
GTX20L-BS <sup>1</sup>	18	6 <sup>7</sup> / <sub>8</sub> <sup>3</sup> / <sub>16</sub> <sup>1</sup> / <sub>6</sub> <sup>1</sup> / <sub>8</sub>	175/87/155		11.2	5.1	4	31.4	0.93	1.8	275

<sup>1</sup> The GTX20 series batteries may be used as an optional upgrade, but some modification to the hold down may be necessary. See battery label for retrofit cautions.

## CB Series

12 VOLT

Battery Type	Capacity AH (10HR)	Dimensions -Inches- L/W/H	Dimensions -Millimeters- L/W/H	Assembly Figure (As per cover polarity)	Weight Lbs. w/o acid	Weight Kgs. w/o acid	Terminal Type- see pg. 4	Acid Volume (Ozs.)	Acid Volume (Liters)	Regular Charge Current (amps)
CB2.5L-C	2.5	3 <sup>3</sup> / <sub>16</sub> <sup>2</sup> / <sub>3</sub> <sup>4</sup> / <sub>1</sub> <sup>8</sup>	80/70/105		1.7	0.8	-	8.1	.23	0.3
CB2.5L-C-1	2.5	3 <sup>3</sup> / <sub>16</sub> <sup>2</sup> / <sub>3</sub> <sup>4</sup> / <sub>1</sub> <sup>8</sup>	80/70/105		1.7	0.8	-	8.1	.23	0.3
CB3L-A	3	3 <sup>7</sup> / <sub>8</sub> <sup>2</sup> / <sub>1</sub> <sup>4</sup> / <sub>4</sub> <sup>3</sup> / <sub>8</sub>	98/56/110		2.5	1.1	6	8.1	.23	0.3
CB3L-B	3	3 <sup>7</sup> / <sub>8</sub> <sup>2</sup> / <sub>1</sub> <sup>4</sup> / <sub>4</sub> <sup>3</sup> / <sub>8</sub>	98/56/110		2.5	1.1	6	8.1	.23	0.3
CB4L-A	4	4 <sup>3</sup> / <sub>4</sub> <sup>2</sup> / <sub>3</sub> <sup>4</sup> / <sub>3</sub> <sup>5</sup> / <sub>8</sub>	120/70/92		2.8	1.3	5	10.1	.30	0.4
CB4L-B	4	4 <sup>3</sup> / <sub>4</sub> <sup>2</sup> / <sub>3</sub> <sup>4</sup> / <sub>3</sub> <sup>5</sup> / <sub>8</sub>	120/70/92		2.8	1.3	5	10.1	.30	0.4
CB5L-B	5	4 <sup>3</sup> / <sub>4</sub> <sup>2</sup> / <sub>3</sub> <sup>8</sup> / <sub>5</sub> <sup>1</sup> / <sub>8</sub>	120/60/130		3.5	1.6	6	12.2	.36	0.5